



COMPRESSOR SPECIFICATIONS

BORE	Ø35 mm
STROKE	22.6 mm
DISPLACEMENT PER REVOLUTION	108 cc/rev
NUMBER OF CYLINDERS	5
MAXIMUM ALLOWABLE r.p.m.	7000 r.p.m.
MAXIMUM ALLOWABLE CONTINUOUS r.p.m.	6000 r.p.m.
REFRIGERANT	HFC134a
OIL(SP-20 OR EQUIV.)	135 cc
ROTATION(CLUTCH SIDE VIEW)	CLOCKWISE
WEIGHT	kg

CLUTCH SPECIFICATIONS

RATED VOLTAGE	DC 12 V
BREAKAWAY TORQUE	2.65 kg-m
MINIMUM ENGAGEMENT VOLTAGE	7.5 V max
POWER CONSUMPTION	48 W (AL)
MAXIMUM ALLOWABLE r.p.m.	7000 r.p.m.
MAXIMUM ALLOWABLE CONTINUOUS r.p.m.	6000 r.p.m.
BELT TYPE	PV
PULLEY DIAMETER	Ø140 mm
WEIGHT	kg

△				MATERIAL	PART NO.	NAME
△					6372	COMPRESSOR
△				THIRD ANGLE PROJECTION	SCALE	1:1
△				DESIGN BY	CHECKED BY	APPROVED BY
△						SD5H11FL6372
△						DRAWING NO. 6372-6000S
No.	REVISION RECORD	BY	DATE			